


- Typical Specifications
1. Rating : 5A120V AC
 2. Insulation Resistance:1,000M min
 3. Dielectric Strength:1,500V RMS
 4. Operating Life : 30,000 cycles



Circuit Diagram

PART NO	vigor
1	300±100

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Copper	Plating silver	—
④	Contact	—	1	F.Ag/C5210	—	—
③	Base	—	1	PA	Black	—
②	Cover	—	1	SPCC	Plating Sn	—
①	Keystoke	—	1	PA	RED	—

APPROVALS	DATE
DRAWN	2015.05.25
CHECKED	
APPROVED	

深圳市裕诚电子有限公司
SHENZHEN YUCHENG ELECTRONICS CO., LTD

WEBSITE	www.ycelectron.com
PART NO.	M3-2268S
SCALE:	1:1
PROJ.	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
TOLERANCES ARE						
	30 ^{±0.15}	±0.30	±0.20	ANGLE	UNIT: mm	SCALE: 1:1
	10-30	±0.20	±0.15	±Z	DRAWING NO.	PROJ.
	5-10	±0.15	±0.10			SHEET 1 OF 1