



NOTE:
 Rating: DC 12V 50mA
 Operating Force: 10±5gf
 Lifetime: 100,000 Cycles

| | |
|--|--------------------------|
| | PART NO. K5-1620UA-01 |
| | K5-1620UN-01 |
| | K5-1620UJ-01 |

| ITEM | PART NAME | TER.NO. | QTY. | MATERIAL | FINISHING | REMARK |
|------|----------------|---------|------|-----------------|-----------|--------|
| ⑤ | Contact Spring | --- | 1 | Phosphor Bronze | Ag Plated | --- |
| ④ | Terminal | --- | 4 | Phosphor Bronze | Ag Plated | --- |
| ③ | Base | --- | 1 | PA46 | Black | --- |
| ② | Cover | --- | 1 | SUS | Natural | --- |
| ① | Slider | --- | 1 | PA46 | Black | --- |

| APPROVALS | DATE |
|-----------------|-----------|
| DRAWN J.X.Zhang | 2013/8/28 |
| CHECKED | |
| APPROVALS | |

| | | | | | |
|-----------------|------------|----------------|-------------|--|-------|
| DRAWN J.X.Zhang | | DATE 2013/8/28 | | WEBSITE www.ycelectron.com | |
| CHECKED | | | | PART NO. M5-1685E | |
| APPROVALS | | | | SCALE: 1:1 | |
| TOLERANCES ARE | | 30~50 ±0.30 | ANGLE | UNIT: mm | PROJ. |
| 10~30 ±0.20 | 5~10 ±0.15 | ±2° | DRAWING NO. | SHEET 1 OF 1 | |

| | | | | | | |
|---------|------|-------|--------------|---------|--------|--------|
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
| | A | | NEW | | | |

深圳市裕诚电子有限公司
 SHENZHEN YUCEHENG ELECTRONICS CO., LTD