


NOTE:

- 1. Rating: AC125V 5A/250V 3A
- 2. Operating force: 100±30gf
- 3. Mechanical Life: 100,000
- 3. Electrical Life: 6000-10,000



Circuit Diagram

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Aluminum rivet	—	1	Aluminum Alloy	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—

APPROVALS		DATE		深圳市裕诚电子有限公司 SHENZHEN YUCHENG ELECTRONICS CO., LTD		
DRAWN	J.X.Zhang	2014/8/19				
CHECKED				WEBSITE	www.ycelectron.com	
APPROVALS				PART NO.	M7-1162K	
TOLERANCES ARE			30~0.1	±0.30	ANGLE	UNIT: mm SCALE: 1:1 PROJ:
			10~20	±0.25	±2'	
			5~10	±0.20		DRAWING NO.
			~ 5	±0.20	SHEET 1 OF 1	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
—	A	—	NEW	—	—	—