








RoHS Compliant

REV. A/0	DESCRIPTION NEW	DESIGN CWF	DATE
----------	-----------------	------------	------

Position(位数)	2P	3P	4P	5P	6P	8P	10P	
DIM.A(长度)	4.14	5.41	6.68	7.95	9.20	11.74	14.28	
DIM.B(长度)	1.27	2.54	3.81	5.08	6.35	8.89	11.43	
PART NO. 盖子/黑色	平推 (P)	M6-PH02P	M6-PH03P	M6-PH04P	M6-PH05P	M6-PH06P	M6-PH08P	M6-PH10P



NOTES:

1.Specification:

- 1.1 Operation force: 1000gf Max.
- 1.2 Operation Temperature: -30℃ to +85℃.
- 1.3 Storage Temperature: -40℃ to +85℃.
- 1.4 Mechanical Life: 3000 cycles operations.
- 1.5 Resistance to Soldering: 250±5℃ for 3-5 Seconds.

2.ELECTRICAL:

- 2.1 Non-switch Rating: 100mA at 50V DC.
- 2.2 Switching Rating: 25mA at 24V DC.
- 2.3 Contact Resistance: Initial 50mΩ Max.  
Contact Resistance: After life 100mΩ Max.
- 2.4 Insulation Resistance: 100MΩ Min at 100VDC.
- 2.5 Dielectric Strength: 300V AC for 60seconds.
- 2.6 Switch Capacitance: 5PF Max at 1MHZ.

①	Actuator	UL94 V0	White
②	Cover	UL94 V0	Black
③	Movable	Beryllium Copper	3μ' Gold
④	Terminal	Brass	1μ' Gold
⑤	Base	UL94 V0	Black
⑥	Terminal Contact	Brass	3μ' Gold
⑦	Mylar	UL94 V0	0.05mm
ITEM	PART NAME	QTY.	MATERIAL FINISHING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF SHENZHEN YUCHENG ELECTRONICS.LTD.AND SHALL NOT BE REPRODUCED,COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF SHENZHEN YUCHENG ELECTRONICS.LTD



深圳市裕诚电子有限公司  
SHENZHEN YUCHENG ELECTRONICS CO.,LTD

APPROVED:	WEI JIE	GENERAL TOLERANCES	TITLE:	DIAL SWITCH SPACING1.27
CHECKED:	HONG JIN YUN	30~以上 ±0.30	PART NO:	M6-HP□□□
DRAWING:	CHEN YA	10~30 ±0.20	WEBSITE:	www.ycelectron.com
		5~10 ±0.15	REV: A	UNIT: mm
		~ 5 ±0.10		SCALE: /
		SHEET: 1 / 1		SHEET: A4